SAFETY DATA SHEET



1. Identification

1. Identification		
Product identifier	Ready Mix Concrete	
Other means of identification		
Synonyms	Agileflow®, Agilia® Screed C, AgrifargeTM 20, 25, 30, 32, AgrifargeTM Plus, AgrifargeTM RP, ArteviaColor®, Chronolia®, Colloidal Concrete, Colored Concrete, Concrete, Concrete Ready Mix, Duraload and Coreforce. ECOPact, ExtensiaTM, Fiber Reinforced Concrete, Flowable Fill, Freshly Mixed Concrete, Gunite, Hydromedia®, HYDROMEDIATM, Lafarge Ready Mix Concrete, Permeable Concrete, Polymer-Portland Cement Concrete, Portland Cement Concrete, RAPIDFORCE ®, Ready Mix, Ready Mix Concrete, Ready Mix Grout, Ready Mix Stucco, Roller-Compacted Concrete, Shotcrete, Thermaflow TM, The Artevia Collection®, UltraCurbTM, UltraDriveTM, UltraFlo-FiITM, UltraFootingTM, UltraHorizontaITM, UltraPatioTM, UltraStampTM, UltraTiltTM, UltraVerticaITM, Weathermix, Agilia®, Agilia® Architectural, Agilia® Vertical, Agilia® Horizontal, Agilia® Industrial, Agilia® BlockFill,Agilia® Screed A – Standard, Agilia® Screed A – Premium, Agilia® Screed A – Ultra, Agilia® Screed A – Fina	
Recommended use	Construction.	
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations. Uses other than the recommended use.	
Manufacturer/Importer/Supplie	er/Distributor information	
Company name	Amrize Inc.	
Address	6509 Airport Road	
	Mississauga, Ontario L4V 157	
Telephone	Eastern Canada: (905) 738-7070	
	Western Canada: (403) 225-5400	
Website	www.amrize.com	
E-mail	sdsinfo@amrize.com	
Emergency telephone number	CHEMTREC within USA and Canada: 1-800-424-9300 CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)	
2. Hazard identification		
Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 1C
noulli huzurdo	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1
	Carcinogenicity (inhalation)	Category 1A
	Specific target organ toxicity - single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity - repeated exposure (inhalation)	Category 2 (Lungs)
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
Label elements		
Signal word	Danger	
Hazard statement		May cause an allergic skin reaction. May cause alation. May cause damage to organs (Lungs) inalation. Harmful to aquatic life

through prolonged or repeated exposure by inhalation. Harmful to aquatic life.

ntil all safety precautions have been read after handling. Use only outdoors or in a d not be allowed out of the workplace. es/protective clothing/eye protection/face
g. IF ON SKIN (or hair): Take off water or shower. IF INHALED: Remove IF IN EYES: Rinse cautiously with water and easy to do. Continue rinsing. ISON CENTRE/doctor if you feel unwell. If on. Take off contaminated clothing and
losed. Store locked up.
regional/national/international regulations.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Quartz		14808-60-7	80 - 100
Calcium hydroxide		1305-62-0	10 - 30
Portland Cement		65997-15-1	10 - 30
Calcium oxide		1305-78-8	1 - 5
Composition comments	All concentrations are in percent by weight. C below reportable limits. Any concentration sho batch variation.		
4. First-aid measures			
Inhalation	Remove victim to fresh air and keep at rest in give artificial respiration. Call a poison centre		
Skin contact	Remove contaminated clothing immediately a or poison control centre immediately. Chemic contaminated clothing before reuse.		
Eye contact	Immediately flush eyes with plenty of water for present and easy to do. Continue rinsing. Cal		
Ingestion	Call a physician or poison control centre immer vomiting occurs, keep head low so that stoma		
Most important symptoms/effects, acute and delayed	Burning pain and severe corrosive skin dama include stinging, tearing, redness, swelling, a blindness could result. May cause respiratory chronic effects.	nd blurred vision. Permanent e	eye damage including
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and tre immediately. While flushing, remove clothes v ambulance. Continue flushing during transpor Symptoms may be delayed.	which do not adhere to affecte	d area. Call an
General information	IF exposed or concerned: Get medical advice (show the label where possible). Ensure that involved, and take precautions to protect ther	medical personnel are aware	of the material(s)
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carb	on dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as th	is will spread the fire.	
Specific hazards arising from the chemical	During fire, gases hazardous to health may b oxides. Carbon oxides. Manganese oxides. S		ts may include: Calcium

 the chemical
 oxides. Carbon oxides. Manganese oxides. Silicon oxides.

 Special protective equipment
 Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special protective equipment and precautions for firefighters

Fire fighting equipment/instructions	Use water spray to cool unopened containers. Water runoff can cause environmental damage.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Will burn if involved in a fire.

6. Accidental release measures

6. Accidental release meas	sures
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for	Prevent product from entering drains.
containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Following product recovery, flush area with water.
	Small Spills: Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. Put material in suitable, covered, labelled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices. Persons susceptible to allergic reactions should not handle this product.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values (TLV)

Components	Туре	Value	Form
Calcium hydroxide (CAS 1305-62-0)	TWA	5 mg/m3	
Calcium oxide (CAS 1305-78-8)	TWA	2 mg/m3	
Portland Cement (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2), as amended

Components	Туре	Value	Form
Calcium hydroxide (CAS 1305-62-0)	TWA	5 mg/m3	
Calcium oxide (CAS 1305-78-8)	TWA	2 mg/m3	
Portland Cement (CAS 65997-15-1)	TWA	10 mg/m3	
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable particles.

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form
Calcium hydroxide (CAS 1305-62-0)	TWA	5 mg/m3	

components	Туре	Value	Form
Calcium oxide (CAS 305-78-8)	TWA	2 mg/m3	
ortland Cement (CAS 5997-15-1)	TWA	1 mg/m3	Respirable.
uartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
anada. Manitoba OELs (Reg. 21			_
omponents	Туре	Value	Form
alcium hydroxide (CAS 305-62-0)	TWA	5 mg/m3	
alcium oxide (CAS 305-78-8)	TWA	2 mg/m3	
ortland Cement (CAS 5997-15-1)	TWA	1 mg/m3	Respirable fraction.
uartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
anada. New Brunswick OELs: T		used on the 1991 and 1997 A	CGIH TLVs and BEIs
ublication (New Brunswick Region omponents	Jiation 91-191) Type	Value	Form
alcium hydroxide (CAS 305-62-0)	TWA	5 mg/m3	
alcium oxide (CAS 305-78-8)	TWA	2 mg/m3	
ortland Cement (CAS 5997-15-1)	TWA	1 mg/m3	Respirable fraction.
euartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
anada. Ontario OELs. (Control c omponents	f Exposure to Biological or Che Type	mical Agents), as amended Value	Form
alcium hydroxide (CAS 305-62-0)	TWA	5 mg/m3	
alcium oxide (CAS 305-78-8)	TWA	2 mg/m3	
ortland Cement (CAS 5997-15-1)	TWA	1 mg/m3	Respirable fraction.
uartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable fraction.
anada. Quebec OELs. (Ministry omponents	of Labor - Regulation respecting Type	g occupational health and sa Value	fety) Form
alcium hydroxide (CAS 305-62-0)	TWA	5 mg/m3	
alcium oxide (CAS 305-78-8)	TWA	2 mg/m3	
ortland Cement (CAS 5997-15-1)	TWA	5 mg/m3	Respirable dust.
		10 mg/m3	Total dust.
uartz (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
anada. Saskatchewan OELs (Oc omponents	cupational Health and Safety Re Type	egulations, 1996, Table 21), a Value	s amended Form
alcium hydroxide (CAS 305-62-0)	15 minute	10 mg/m3	
···· ·· ·· ·· ·· ·· ·· ·· ·· ·· ·· ·· ·	8 hour	5 mg/m3	
alcium oxide (CAS 305-78-8)	15 minute	4 mg/m3	
	8 hour	2 mg/m3	

Canada. Saskatchewan OE Components	Туре	Value	Form
Portland Cement (CAS 65997-15-1)	15 minute	20 mg/m3	
	8 hour	10 mg/m3	
Quartz (CAS 14808-60-7)	8 hour	0.05 mg/m3	Respirable fraction.
Biological limit values	No biological exposure limits noted for th	ie ingredient(s).	
Exposure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.		
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.		
Individual protection measures	s, such as personal protective equipment		
Eye/face protection	Wear safety glasses with side shields (or	r goggles) and a face shield	
Skin protection			
Hand protection	Wear appropriate chemical resistant glov supplier.	ves. Suitable gloves can be	recommended by the glove
Other	Wear appropriate chemical resistant clot	hing. Use of an impervious	apron is recommended.
Respiratory protection	If engineering controls do not maintain ai limits (where applicable) or to an accepta been established), an approved respirato protective equipment should be in accord	able level (in countries wher or must be worn. Selection a	e exposure limits have not and use of respiratory
Thermal hazards	Wear appropriate thermal protective clot	hing, when necessary.	
General hygiene considerations	Observe any medical surveillance requir measures, such as washing after handlir smoking. Routinely wash work clothing a Contaminated work clothing should not b	ng the material and before e and protective equipment to	ating, drinking, and/or remove contaminants.

9. Physical and chemical properties

3. Filysical and chemical p	noperties
Physical state	Solid.
Form	Paste.
Colour	Grey to black.
Odour	Odourless.
Odour threshold	Not applicable.
Melting point/freezing point	Property has not been measured.
Boiling point or initial boiling point and boiling range	> 1000 °C (> 1832 °F)
Flammability	Will burn if involved in a fire.
Upper/lower flammability or expl	losive limits
Explosive limit - lower (%)	Not applicable, material is a solid.
Explosive limit – upper (%)	Not applicable, material is a solid.
Flash point	Not applicable, material is a solid.
Auto-ignition temperature	Not applicable, material is a solid.
Decomposition temperature	Property has not been measured.
рН	12 - 13
pH concentration	Property has not been measured.
Kinematic viscosity	Not applicable, material is a solid.
Solubility	
Solubility (water)	Slightly soluble
Partition coefficient (n-octanol/water) (log value)	Not applicable for inorganic substances.

Vapour pressure	Property has not been measured.
Density and/or relative density	
Density	Property has not been measured.
Relative density	1.9 - 2.4
Relative density temperature	Property has not been measured.
Vapour density	Not applicable, material is a solid.
Particle characteristics	
Particle size	Property has not been measured.
Other information	
Evaporation rate	Not applicable, material is a solid.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
Viscosity	Not applicable, material is a solid.
10. Stability and reactivity	,
Reactivity	Reacts violently with strong acids. This product may react with oxidizing agents.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials. Do not mix with other chemicals.
Incompatible materials	Acids. Powerful oxidizers. Oxidizing agents. Chlorine. Fluorine. Maleic anhydride. Nitroethane. Nitromethane. Nitroparaffins. Nitropropane. Phosphorus. Ammonium salts. Aluminum metal. Hydrofluoric acid. Boron trifluoride. Chlorine trifluoride. Magnesium trifluoride. Oxygen difluoride.
Hazardous decomposition products	No hazardous decomposition products are known. In the event of fire: See Section 5.

11. Toxicological information

Information on likely routes of exposure

······································	
Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause cancer by inhalation. May cause irritation to the respiratory system.
Skin contact	Causes severe skin burns. May cause an allergic skin reaction.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns.
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Coughing. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity

Not expected to be acutely toxic.

Components	Species		Test Results	
Calcium hydroxide (C	AS 1305-62-0)			
Acute				
Oral				
LD50	Rat		7340 mg/kg	
Calcium oxide (CAS	1305-78-8)			
Acute				
Oral				
LD50	Rat		> 2000 mg/kg No deaths concentration.	s occured at this
Portland Cement (CA	S 65997-15-1)			
Acute				
Dermal				
LD50	Rat		> 2000 mg/kg	
Ready Mix Concrete				SDS Canada
972097	Version #: 01	Revision date: -	Issue date: 28-May-2025	6 / 10

	Species	Test Results
Inhalation		
dust/mist		
LC50	Rat	> 6.04 mg/l, 4 Hours
Oral		
LD50	Rat	> 1848 mg/kg
Quartz (CAS 14808-60-7)		
<u>Chronic</u>		
Inhalation		
LOEC	Human	0.0563 mg/m3
Skin corrosion/irritation	Causes severe skin burns	ð.
Serious eye damage/eye rritation	Causes serious eye dama	age.
Respiratory or skin sensitisatio	n	
Canada - Alberta OELs: Irrit	tant	
Calcium hydroxide (CAS Calcium oxide (CAS 130 Portland Cement (CAS 6	5-78-8)	Irritant Irritant Irritant
Respiratory sensitisation	Not a respiratory sensitise	er.
Skin sensitisation	May cause an allergic skir	n reaction.
Germ cell mutagenicity	No data available to indica mutagenic or genotoxic.	ate product or any components present at greater than 0.1% are
	overall evaluation, IARC r	I sources can cause lung cancer in humans. However in making the noted that "carcinogenicity was not detected in all industrial arcinogenicity may be dependent on inherent characteristics of the
	crystalline silica or on external polymorphs." (IARC Mon- humans, Silica, silicates d 2003, SCOEL (the EU Sci main effect in humans of t sufficient information to co silicosis (and, apparently, in the ceramic industry). risk" (SCOEL SUM Doc protection against silicosis occupational exposure lim	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that th the inhalation of respirable crystalline silica dust is silicosis. "There is ponclude that the relative risk of lung cancer is increased in persons with
ACGIH Carcinogens	crystalline silica or on external polymorphs." (IARC Mon- humans, Silica, silicates d 2003, SCOEL (the EU Sci main effect in humans of t sufficient information to co silicosis (and, apparently, in the ceramic industry). risk" (SCOEL SUM Doc protection against silicosis occupational exposure lim	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries an Therefore, preventing the onset of silicosis will also reduce the cancer 94-final, June 2003) According to the current state of the art, worker s can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to
Portland Cement (CAS 6	crystalline silica or on external polymorphs." (IARC Mon- humans, Silica, silicates d 2003, SCOEL (the EU Sci main effect in humans of t sufficient information to co silicosis (and, apparently, in the ceramic industry). risk" (SCOEL SUM Doc protection against silicosis occupational exposure lim respirable dust and respira	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries and Therefore, preventing the onset of silicosis will also reduce the cancer 94-final, June 2003) According to the current state of the art, worker is can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to able crystalline silica should be monitored and controlled. A4 Not classifiable as a human carcinogen.
Portland Cement (CAS 6 Quartz (CAS 14808-60-7	crystalline silica or on external polymorphs." (IARC Mon- humans, Silica, silicates d 2003, SCOEL (the EU Sci main effect in humans of t sufficient information to co silicosis (and, apparently, in the ceramic industry). risk" (SCOEL SUM Doc protection against silicosis occupational exposure lim respirable dust and respira 55997-15-1)	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries and Therefore, preventing the onset of silicosis will also reduce the cancer .94-final, June 2003) According to the current state of the art, worker is can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to able crystalline silica should be monitored and controlled.
Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Alberta OELs: Car	crystalline silica or on external polymorphs." (IARC Momhumans, Silica, silicates d 2003, SCOEL (the EU Scimain effect in humans of t sufficient information to consilicosis (and, apparently, in the ceramic industry). Trisk" (SCOEL SUM Doc protection against silicosis occupational exposure limit respirable dust and respirations and respirations). (S5997-15-1)	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries and Therefore, preventing the onset of silicosis will also reduce the cancer 94-final, June 2003) According to the current state of the art, worker is can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to able crystalline silica should be monitored and controlled. A4 Not classifiable as a human carcinogen. A2 Suspected human carcinogen.
Portland Cement (CAS 6 Quartz (CAS 14808-60-7	crystalline silica or on external polymorphs." (IARC Mon- humans, Silica, silicates d 2003, SCOEL (the EU Sci main effect in humans of t sufficient information to co- silicosis (and, apparently, in the ceramic industry). risk" (SCOEL SUM Doc protection against silicosis occupational exposure lim respirable dust and respira (55997-15-1) 7) rcinogen category 7)	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries and Therefore, preventing the onset of silicosis will also reduce the cancer 94-final, June 2003) According to the current state of the art, worker is can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to able crystalline silica should be monitored and controlled. A4 Not classifiable as a human carcinogen.
Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Alberta OELs: Ca Quartz (CAS 14808-60-7	crystalline silica or on external polymorphs." (IARC Momhumans, Silica, silicates d 2003, SCOEL (the EU Scimain effect in humans of t sufficient information to consilicosis (and, apparently, in the ceramic industry). "risk" (SCOEL SUM Doc protection against silicosis occupational exposure limit respirable dust and respirable dust and respirational exposure limit respirati exposure limit respirational exposure limit respi	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries and Therefore, preventing the onset of silicosis will also reduce the cancer 94-final, June 2003) According to the current state of the art, worker is can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to able crystalline silica should be monitored and controlled. A4 Not classifiable as a human carcinogen. A2 Suspected human carcinogen.
Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Alberta OELs: Can Quartz (CAS 14808-60-7 Canada - Manitoba OELs: c Portland Cement (CAS 6 Quartz (CAS 14808-60-7	crystalline silica or on external polymorphs." (IARC Momhumans, Silica, silicates d 2003, SCOEL (the EU Scimain effect in humans of t sufficient information to consilicosis (and, apparently, in the ceramic industry). Trisk" (SCOEL SUM Doc protection against silicosis occupational exposure limit respirable dust and respirable dust and respiration constrained and respirational exposure limit respirable dust and respirational exposure limit respirational exposure limit respirable dust and respirational exposure limit respirational exposure limit respirable dust and respirational exposure limit respiration	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries an Therefore, preventing the onset of silicosis will also reduce the cancer .94-final, June 2003) According to the current state of the art, worker is can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to able crystalline silica should be monitored and controlled. A4 Not classifiable as a human carcinogen. A2 Suspected human carcinogen. Suspected human carcinogen.
Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Alberta OELs: Car Quartz (CAS 14808-60-7 Canada - Manitoba OELs: c Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Quebec OELs: Ca	crystalline silica or on external polymorphs." (IARC Momhumans, Silica, silicates d 2003, SCOEL (the EU Scimain effect in humans of t sufficient information to consilicosis (and, apparently, in the ceramic industry). Trisk" (SCOEL SUM Doc protection against silicosis occupational exposure limit respirable dust and respirable dust and respirational exposure limit res	 ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries an Therefore, preventing the onset of silicosis will also reduce the cancer 94-final, June 2003) According to the current state of the art, worker is can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to able crystalline silica should be monitored and controlled. A4 Not classifiable as a human carcinogen. A2 Suspected human carcinogen. Not classifiable as a human carcinogen. Suspected human carcinogen.
Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Alberta OELs: Car Quartz (CAS 14808-60-7 Canada - Manitoba OELs: c Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Quebec OELs: Ca Quartz (CAS 14808-60-7 IARC Monographs. Overall	crystalline silica or on exterpolymorphs." (IARC Momhumans, Silica, silicates d 2003, SCOEL (the EU Scimain effect in humans of t sufficient information to co silicosis (and, apparently, in the ceramic industry). Trisk" (SCOEL SUM Doc protection against silicosis occupational exposure lim respirable dust and respira (55997-15-1) () crinogen category () sarcinogenicity (55997-15-1) () rrcinogen category () Evaluation of Carcinogeni	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries an Therefore, preventing the onset of silicosis will also reduce the cancer 94-final, June 2003) According to the current state of the art, worker is can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to able crystalline silica should be monitored and controlled. A4 Not classifiable as a human carcinogen. A2 Suspected human carcinogen. Suspected human carcinogen. Suspected human carcinogen. Suspected human carcinogen. Suspected human carcinogen. Suspected carcinogenic effect in humans. city
Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Alberta OELs: Can Quartz (CAS 14808-60-7 Canada - Manitoba OELs: C Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Quebec OELs: Ca Quartz (CAS 14808-60-7 IARC Monographs. Overall Quartz (CAS 14808-60-7	crystalline silica or on exterpolymorphs." (IARC Momhumans, Silica, silicates d 2003, SCOEL (the EU Scimain effect in humans of t sufficient information to co silicosis (and, apparently, in the ceramic industry). risk" (SCOEL SUM Doc protection against silicosis occupational exposure lim respirable dust and respira (5997-15-1) () rcinogen category () sarcinogenicity (5997-15-1) () rcinogen category () Evaluation of Carcinogenic ()	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries an Therefore, preventing the onset of silicosis will also reduce the cancer 94-final, June 2003) According to the current state of the art, worker is can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to able crystalline silica should be monitored and controlled. A4 Not classifiable as a human carcinogen. A2 Suspected human carcinogen. Suspected human carcinogen. Suspected human carcinogen. Suspected human carcinogen. Suspected carcinogenic effect in humans. city 1 Carcinogenic to humans.
Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Alberta OELs: Car Quartz (CAS 14808-60-7 Canada - Manitoba OELs: C Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Quebec OELs: Ca Quartz (CAS 14808-60-7 IARC Monographs. Overall Quartz (CAS 14808-60-7 US. National Toxicology Press	crystalline silica or on external polymorphs." (IARC Momhumans, Silica, silicates d 2003, SCOEL (the EU Scimain effect in humans of t sufficient information to consilicosis (and, apparently, in the ceramic industry). Trisk" (SCOEL SUM Doc protection against silicosis occupational exposure limit respirable dust and respirable dust and respirable dust and respirable for the category of the cate	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries an Therefore, preventing the onset of silicosis will also reduce the cancer .94-final, June 2003) According to the current state of the art, worker is can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to able crystalline silica should be monitored and controlled. A4 Not classifiable as a human carcinogen. A2 Suspected human carcinogen. Suspected human carcinogen. Suspected human carcinogen. Suspected human carcinogen. Current suspected human carcinogen. Suspected carcinogenic effect in humans. city 1 Carcinogenic to humans. rcinogens
Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Alberta OELs: Car Quartz (CAS 14808-60-7 Canada - Manitoba OELs: Ca Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Quebec OELs: Ca Quartz (CAS 14808-60-7 IARC Monographs. Overall Quartz (CAS 14808-60-7 US. National Toxicology Pro Quartz (CAS 14808-60-7	crystalline silica or on exterpolymorphs." (IARC Momhumans, Silica, silicates d 2003, SCOEL (the EU Scimain effect in humans of t sufficient information to co silicosis (and, apparently, in the ceramic industry) risk" (SCOEL SUM Doc protection against silicosis occupational exposure lim respirable dust and respira (S5997-15-1) () rcinogen category () sarcinogenicity (S5997-15-1) () rcinogen category () Evaluation of Carcinogenic () ogram (NTP) Report on Ca	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries an Therefore, preventing the onset of silicosis will also reduce the cancer 94-final, June 2003) According to the current state of the art, worker s can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to able crystalline silica should be monitored and controlled. A4 Not classifiable as a human carcinogen. A2 Suspected human carcinogen. Suspected human carcinogen. Suspected human carcinogen. Suspected human carcinogen. Suspected carcinogenic effect in humans. city 1 Carcinogenic to humans. rcinogens Known To Be Human Carcinogen.
Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Alberta OELs: Car Quartz (CAS 14808-60-7 Canada - Manitoba OELs: Ca Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Quebec OELs: Ca Quartz (CAS 14808-60-7 IARC Monographs. Overall Quartz (CAS 14808-60-7 US. National Toxicology Pro Quartz (CAS 14808-60-7 Reproductive toxicity	crystalline silica or on external polymorphs." (IARC Momhumans, Silica, silicates d 2003, SCOEL (the EU Scimain effect in humans of t sufficient information to consilicosis (and, apparently, in the ceramic industry). Trisk" (SCOEL SUM Doc protection against silicosis occupational exposure limit respirable dust and respiration of carcinogenicity (S5997-15-1) (This product is not expect for the carcinogenicity (Statement of Carcinogenicity (Statement	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries an Therefore, preventing the onset of silicosis will also reduce the cancer 94-final, June 2003) According to the current state of the art, worker s can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to able crystalline silica should be monitored and controlled. A4 Not classifiable as a human carcinogen. A2 Suspected human carcinogen. Suspected human carcinogen. Suspected human carcinogen. Suspected human carcinogen. Suspected carcinogenic effect in humans. city 1 Carcinogenic to humans. rcinogens Known To Be Human Carcinogen. ted to cause reproductive or developmental effects.
Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Alberta OELs: Car Quartz (CAS 14808-60-7 Canada - Manitoba OELs: Ca Portland Cement (CAS 6 Quartz (CAS 14808-60-7 Canada - Quebec OELs: Ca Quartz (CAS 14808-60-7 IARC Monographs. Overall Quartz (CAS 14808-60-7 US. National Toxicology Press	crystalline silica or on exterpolymorphs." (IARC Momhumans, Silica, silicates d 2003, SCOEL (the EU Scimain effect in humans of t sufficient information to co silicosis (and, apparently, in the ceramic industry) risk" (SCOEL SUM Doc protection against silicosis occupational exposure lim respirable dust and respira (S5997-15-1) () rcinogen category () sarcinogenicity (S5997-15-1) () rcinogen category () Evaluation of Carcinogenic () ogram (NTP) Report on Ca	ernal factors affecting its biological activity or distribution of its ographs on the evaluation of the carcinogenic risks of chemicals to lust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June ientific Committee on Occupational Exposure Limits) concluded that the the inhalation of respirable crystalline silica dust is silicosis. "There is onclude that the relative risk of lung cancer is increased in persons with not in employees without silicosis exposed to silica dust in quarries an Therefore, preventing the onset of silicosis will also reduce the cancer 94-final, June 2003) According to the current state of the art, worker s can be consistently assured by respecting the existing regulatory nits. May cause cancer by inhalation. Occupational exposure to able crystalline silica should be monitored and controlled. A4 Not classifiable as a human carcinogen. A2 Suspected human carcinogen. Suspected human carcinogen. Suspected human carcinogen. Suspected human carcinogen. Suspected carcinogenic effect in humans. city 1 Carcinogenic to humans. rcinogens Known To Be Human Carcinogen. ted to cause reproductive or developmental effects.

Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

otoxicity	Harmful to	o aquatic life.	
Components		Species	Test Results
Calcium hydroxide (CAS 13	05-62-0)		
Aquatic			
Acute			
Fish	LC50	Zambezi barbel (Clarias gariepinus)	33.9 mg/l, 96 hours
Portland Cement (CAS 6599	97-15-1)		
Aquatic			
Acute			
Algae	EC50	Desmodesmus subspicatus	28.2 mg/l, 72 Hours
	NOEC	Desmodesmus subspicatus	6.25 mg/l, 72 Hours
Crustacea	EC50	Daphnia magna	> 100 mg/l, 48 Hours
Chronic			
Crustacea	NOEC	Daphnia magna	50 mg/l, 21 days
Terrestrial			
Acute			
Other	EC50	Other bacteria soil microorganisms	743 mg/l, 3 Hours
rsistence and degradability	No data is	s available on the degradability of this produc	ct.
oaccumulative potential	No data a	vailable.	
obility in soil	The produ	uct is slightly soluble in water. Not expected t	o be mobile in soil.
her adverse effects	No data a	vailable.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

TDG

100	
UN number	UN3262
UN proper shipping name	CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (Calcium hydroxide)
Transport hazard class(es)	
Class	8
Subsidiary hazard	-
Packing group	III
Environmental hazards	No.
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.
ΙΑΤΑ	
UN number	UN3262
UN proper shipping name	Corrosive solid, basic, inorganic, n.o.s. (Calcium hydroxide)
Transport hazard class(es)	
Class	8

Subsidiary hazard	-	
Packing group		
Environmental hazards ERG Code	No. 8L	
	Read safety instructions, SDS and emergency procedures before handlin	a.
IMDG	5 5 5 1	0
UN number	UN3262	
UN proper shipping name	CORROSIVE SOLID, BASIC, INORGANIC, N.O.S. (Calcium hydroxide)	
Transport hazard class(es) Class	8	
Subsidiary hazard	- -	
Packing group	III	
Environmental hazards		
Marine pollutant	No.	
EmS Special processions for user	F-A, S-B Read sofety instructions, SDS and emergency precedures before handlin	a
Transport in bulk according to	Read safety instructions, SDS and emergency procedures before handlin Not applicable.	g.
Annex II of MARPOL 73/78 and		
the IBC Code		
15. Regulatory information		
Canadian regulations	This product has been classified in accordance with the hazard criteria of contains all the information required by the HPR.	the HPR and the SDS
Controlled Drugs and Substa	ances Act	
Not regulated.		
Export Control List (CEPA 19	999, Schedule 3)	
Not listed.		
Greenhouse Gases Not listed.		
Precursor Control Regulation	ns	
Not regulated.		
International regulations		
Stockholm Convention		
Not applicable.		
Rotterdam Convention		
Not applicable.		
Kyoto Protocol		
Not applicable. Montreal Protocol		
Not applicable.		
Basel Convention		
Not applicable.		
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Country(s) or region

Inventory name

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	28-May-2025
Revision date	-
Version No.	01
Disclaimer	Amrize Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.