

SAFETY DATA SHEET

1. Identification

Product identifier	Portland Cement
Other means of identification	
Synonyms	Cement * Hydraulic Cement * Oil Well Cement * Antique White Cement * Portland Limestone Cement * Portland Cement Type I, IA, IE, I/II, II, IIA, II L.A., III, IIIA, IV, IVA, V, VA, 10, 20, 30, 40, 50, GU, GUL, MS, MSL, HE, HEL, HS, HSL, OWH, OWG * OW Class G HSR * ONECEM® * INFINICEM * EcoPlanet® * White Cement * Trinity White Cement
Recommended use	Construction.
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.
Manufacturer/Importer/Supplier/Distributor information	
Company Name	Amrize Inc.
Address	8700 W Bryn Mawr Ave, Suite 300 Chicago, IL 60631
Telephone	(773) 372-1000
Website	www.amrize.com
E-mail	sdsinfo@amrize.com
Emergency Telephone Number	CHEMTREC within USA and Canada: 1-800-424-9300 CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. Hazard(s) identification

Hazards for the product as sold

Physical hazards Not classified.

Hazards for the product as sold

Health hazards	Skin corrosion/irritation	Category 1
	Serious eye damage/eye irritation	Category 1
	Sensitization, skin	Category 1
	Carcinogenicity (inhalation)	Category 1A

Hazards for the product as sold

Environmental hazards Hazardous to the aquatic environment, acute hazard Category 3

Hazards for the product as sold

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement

Causes severe skin burns and eye damage. May cause an allergic skin reaction. May cause cancer by inhalation. Harmful to aquatic life.

Precautionary statement

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash thoroughly after handling. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.

Response

If swallowed: Rinse mouth. Do NOT induce vomiting. If inhaled: Remove person to fresh air and keep comfortable for breathing. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Cement, portland, chemicals	65997-15-1	100
Limestone	1317-65-3	10 - 15
Calcium sulfate dihydrate	13397-24-5	1 - 10
Calcium oxide	1305-78-8	1 - 5
Magnesium Oxide	1309-48-4	1 - 5
Quartz silica	14808-60-7	0.1 - 1

Composition comments

All concentrations are in percent by weight. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4. First-aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration. Call a poison center or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.

Ingestion

Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Most important symptoms/effects, acute and delayed

Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed. Combustion products may include: Calcium oxides. Carbon oxides. Magnesium oxides. Silicon oxides. Sulfur oxides (SO_x).

Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Will burn if involved in a fire.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Do not breathe dust. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	<p>Large Spills: Stop the flow of material, if this is without risk. Following product recovery, flush area with water.</p> <p>Small Spills: Clean surface thoroughly to remove residual contamination.</p> <p>Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.</p>
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices. Persons susceptible to allergic reactions should not handle this product.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components	Type	Value
Quartz silica (CAS 14808-60-7)	TWA	0.05 mg/m ³

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium oxide (CAS 1305-78-8)	PEL	5 mg/m ³	
Calcium sulfate dihydrate (CAS 13397-24-5)	PEL	5 mg/m ³	Respirable fraction.
Cement, portland, chemicals (CAS 65997-15-1)	PEL	15 mg/m ³ 5 mg/m ³	Total dust. Respirable fraction.
Limestone (CAS 1317-65-3)	PEL	15 mg/m ³ 5 mg/m ³	Total dust. Respirable fraction.
Magnesium Oxide (CAS 1309-48-4)	PEL	15 mg/m ³ 15 mg/m ³	Total dust. Total particulate.

US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Components	Type	Value	Form
Calcium sulfate dihydrate (CAS 13397-24-5)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
Cement, portland, chemicals (CAS 65997-15-1)	TWA	15 mppcf	Respirable fraction.
		50 mppcf	
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
Magnesium Oxide (CAS 1309-48-4)	TWA	15 mppcf	Respirable fraction.
		5 mg/m3	Respirable fraction.
Quartz silica (CAS 14808-60-7)	TWA	15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Quartz silica (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values (TLV)

Components	Type	Value	Form
Calcium oxide (CAS 1305-78-8)	TWA	2 mg/m3	
Calcium sulfate dihydrate (CAS 13397-24-5)	TWA	10 mg/m3	Inhalable fraction.
Cement, portland, chemicals (CAS 65997-15-1)	TWA	1 mg/m3	Respirable fraction.
Magnesium Oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.
Quartz silica (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.

NIOSH. Immediately Dangerous to Life or Health (IDLH) Values, as amended

Components	Type	Value
Calcium oxide (CAS 1305-78-8)	IDLH	25 mg/m3
Cement, portland, chemicals (CAS 65997-15-1)	IDLH	5000 mg/m3
Magnesium Oxide (CAS 1309-48-4)	IDLH	750 mg/m3
Quartz silica (CAS 14808-60-7)	IDLH	50 mg/m3

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Calcium oxide (CAS 1305-78-8)	TWA	2 mg/m3	

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Calcium sulfate dihydrate (CAS 13397-24-5)	TWA	5 mg/m3	Respirable.
Cement, portland, chemicals (CAS 65997-15-1)	TWA	10 mg/m3 5 mg/m3	Total Respirable.
Limestone (CAS 1317-65-3)	TWA	10 mg/m3 5 mg/m3	Total Respirable.
Quartz silica (CAS 14808-60-7)	TWA	10 mg/m3 0.05 mg/m3	Total Respirable dust.
Biological limit values	No biological exposure limits noted for the ingredient(s).		
Exposure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.		
Appropriate engineering controls	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Eye wash facilities and emergency shower must be available when handling this product.		
Individual protection measures, such as personal protective equipment			
Eye/face protection	Wear safety glasses with side shields (or goggles) and a face shield.		
Skin protection			
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.		
Skin protection			
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.		
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.		
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.		
General hygiene considerations	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.		

9. Physical and chemical properties

Physical state	Solid.
Form	Powder.
Color	Gray to white.
Odor	Odorless.
Odor threshold	Not applicable.
Melting point/freezing point	Property has not been measured.
Boiling point or initial boiling point and boiling range	> 1832 °F (> 1000 °C)
Flammability	Will burn if involved in a fire.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not applicable, material is a solid.
Explosive limit - upper (%)	Not applicable, material is a solid.

Flash point	Not applicable, material is a solid.
Auto-ignition temperature	Not applicable, material is a solid.
Decomposition temperature	Property has not been measured.
pH	12 - 13
pH concentration	Property has not been measured.
Kinematic viscosity	Not applicable, material is a solid.
Solubility	
Solubility (water)	Slightly soluble
Partition coefficient (n-octanol/water)	Not applicable, material is inorganic.
Vapor pressure	Property has not been measured.
Vapor pressure temp.	Property has not been measured.
Density and/or relative density	
Density	Property has not been measured.
Relative density	3.15 (water = 1)
Relative density temperature	Property has not been measured.
Vapor density	Not applicable, material is a solid.
Particle characteristics	Property has not been measured.
Other information	
Evaporation rate	Not applicable, material is a solid.
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Viscosity	Not applicable, material is a solid.

10. Stability and reactivity

Reactivity	Reacts violently with strong acids. This product may react with oxidizing agents.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials. Do not mix with other chemicals.
Incompatible materials	Acids. Ammonium salts. Aluminum metal. Oxidizing agents. Fluorine. Hydrofluoric acid. Boron trifluoride. Chlorine trifluoride. Oxygen difluoride. manganese trifluoride
Hazardous decomposition products	No hazardous decomposition products are known. In the event of fire: See Section 5.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause cancer by inhalation. May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	Causes severe skin burns. May cause an allergic skin reaction.
Eye contact	Causes serious eye damage.
Ingestion	Causes digestive tract burns.
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Coughing. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity	Not expected to be acutely toxic.
	Acute toxicity information is not available for all components; LC50 and LD50 data are unavailable for components not listed.

Components	Species	Test Results
Calcium oxide (CAS 1305-78-8)		
Acute		
Oral		
LD50	Rat	> 2000 mg/kg No deaths occurred at this concentration.
Cement, portland, chemicals (CAS 65997-15-1)		
Acute		
Dermal		
LD50	Rat	> 2000 mg/kg
Inhalation		
<i>dust/mist</i>		
LC50	Rat	> 6.04 mg/l, 4 Hours
Oral		
LD50	Rat	> 1848 mg/kg
Quartz silica (CAS 14808-60-7)		
Chronic		
Inhalation		
LOEC	Human	0.0563 mg/m ³
Skin corrosion/irritation	Causes severe skin burns.	
Serious eye damage/eye irritation	Causes serious eye damage.	
Respiratory or skin sensitization		
Respiratory sensitization	Not a respiratory sensitizer.	
Skin sensitization	May cause an allergic skin reaction.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	
Carcinogenicity	In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer by inhalation. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Quartz silica (CAS 14808-60-7)	1	Carcinogenic to humans.
NTP Report on Carcinogens		
Quartz silica (CAS 14808-60-7)	Known To Be Human Carcinogen.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)		
Quartz silica (CAS 14808-60-7)	Cancer	
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.	
Specific target organ toxicity - repeated exposure	Not classified.	

Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.
Further information	None known.

12. Ecological information

Ecotoxicity	Harmful to aquatic life.
--------------------	--------------------------

Components	Species	Test Results
Calcium sulfate dihydrate (CAS 13397-24-5)		
Aquatic		
Fish	LC50	Fathead minnow (Pimephales promelas)
> 1970 mg/l, 96 hours		
Cement, portland, chemicals (CAS 65997-15-1)		
Aquatic		
<i>Acute</i>		
Algae	EC50	Desmodesmus subspicatus
	NOEC	Desmodesmus subspicatus
Crustacea	EC50	Daphnia magna
28.2 mg/l, 72 Hours		
<i>Chronic</i>		
Crustacea	NOEC	Daphnia magna
6.25 mg/l, 72 Hours		
> 100 mg/l, 48 Hours		
Terrestrial		
<i>Acute</i>		
Other	EC50	Other bacteria soil microorganisms
50 mg/l, 21 days		
743 mg/l, 3 Hours		
Persistence and degradability	The product contains inorganic compounds which are not biodegradable.	
Bioaccumulative potential	No data available.	
Mobility in soil	The product is slightly soluble in water. Not expected to be mobile in soil.	
Other adverse effects	No data available.	

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	
Hazardous waste code	Dispose in accordance with all applicable regulations.
Waste from residues / unused products	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Contaminated packaging	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

IMO instruments

15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated "active".

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz silica (CAS 14808-60-7)	Cancer
	lung effects
	immune system effects
	kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical

Classified hazard categories	Skin corrosion or irritation
	Serious eye damage or eye irritation
	Respiratory or skin sensitization
	Carcinogenicity

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Not regulated.

US state regulations

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Quartz silica (CAS 14808-60-7)

US. Massachusetts RTK - Substance List

Calcium oxide (CAS 1305-78-8)
Calcium sulfate dihydrate (CAS 13397-24-5)
Cement, portland, chemicals (CAS 65997-15-1)
Limestone (CAS 1317-65-3)
Magnesium Oxide (CAS 1309-48-4)
Quartz silica (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Calcium oxide (CAS 1305-78-8)

Calcium sulfate dihydrate (CAS 13397-24-5)

Cement, portland, chemicals (CAS 65997-15-1)

Limestone (CAS 1317-65-3)

Magnesium Oxide (CAS 1309-48-4)

Quartz silica (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Calcium oxide (CAS 1305-78-8)

Calcium sulfate dihydrate (CAS 13397-24-5)

Cement, portland, chemicals (CAS 65997-15-1)
Limestone (CAS 1317-65-3)
Magnesium Oxide (CAS 1309-48-4)
Quartz silica (CAS 14808-60-7)

US. Rhode Island RTK

Calcium oxide (CAS 1305-78-8)
Calcium sulfate dihydrate (CAS 13397-24-5)
Cement, portland, chemicals (CAS 65997-15-1)
Limestone (CAS 1317-65-3)
Magnesium Oxide (CAS 1309-48-4)
Quartz silica (CAS 14808-60-7)

California Proposition 65



WARNING: This product can expose you to Quartz silica, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz silica (CAS 14808-60-7)

Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	30-May-2025
Revision date	18-November-2025
Version #	02
HMIS® ratings	Health: 3* Flammability: 1 Physical hazard: 0
Disclaimer	Amrize Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.