SAFETY DATA SHEET



1. Identification

Product identifier	Blended Supplementary Cementitious Material (SCM)	
Other means of identification		
Synonyms	BMb, Precast Pro, Pozzolite, NewCem® Plus, Alk10 MaxCem®	
Recommended use	Construction.	
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations. Uses other than the recommended use.	

Manufacturer/Importer/Supplier/Distributor information

Company Name	Amrize Inc.
Address	8700 W Bryn Mawr Ave, Suite 300
	Chicago, IL 60631
Telephone	(773) 372-1000
Website	www.amrize.com
E-mail	sdsinfo@amrize.com
Emergency Telephone Number	CHEMTREC within USA and Canada: 1-800-424-9300
	CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. Hazard(s) identification

Physical hazards	Not classified.	
Health hazards	Skin corrosion/irritation	Category 2
	Serious eye damage/eye irritation	Category 1
	Carcinogenicity (inhalation)	Category 1A
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
	Specific target organ toxicity, repeated exposure (inhalation)	Category 2 (Lungs)
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	
Hazard statement	Causes skin irritation. Causes serious eye damage. May cause respiratory irritation. May cause cancer by inhalation. May cause damage to organs (Lungs) through prolonged or repeated exposure by inhalation. Harmful to aquatic life.	
Precautionary statement		
Prevention		handle until all safety precautions have been read poroughly after handling. Use only outdoors or in a conment. Wear protective gloves/protective
Response	If on skin: Wash with plenty of water. If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin	

irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before

reuse.

Storage	Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	None.

3. Composition/information on ingredients

Mixtures

WINTUI 65		
Chemical name	CAS number	%
Calcium oxide	1305-78-8	1 - 55
Calcium sulfate	7778-18-9	≤ 22
Magnesium Oxide	1309-48-4	≤ 20
Quartz	14808-60-7	≤ 15
Limestone	1317-65-3	≤ 14
Composition comments	All concentrations are in percent by weight. Any concentration shown as a range is to protect confidentiality or is due to batch variation.	
4. First-aid measures		
Inhalation	Remove victim to fresh air and keep at rest in a position comfortable for bro give artificial respiration. Call a poison center or doctor/physician if you fee	
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skir medical advice/attention. Wash contaminated clothing before reuse.	n irritation occurs: Get
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.	
Ingestion	Rinse mouth. Get medical attention if symptoms occur.	
Most important symptoms/effects, acute and delayed	Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.	
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.	
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.	
5. Fire-fighting measures		
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).	
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.	
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed. Combustion products may include: Silicon oxides. Calcium oxides. Magnesium oxides. Sulfur oxides.	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be wor	rn in case of fire.
Fire fighting equipment/instructions	Use water spray to cool unopened containers. Water runoff can cause env	ironmental damage.
Specific methods	Use standard firefighting procedures and consider the hazards of other inv	olved materials.
General fire hazards	No unusual fire or explosion hazards noted.	
6. Accidental release meas	SUIRES	

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for	Prevent product from entering drains.	
containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Following product recovery, flush area with water.	
	Small Spills: Clean surface thoroughly to remove residual contamination.	
	Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.	
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.	
7. Handling and storage		
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.	
Conditions for safe storage, including any incompatibilities	Store locked up. Store in a well-ventilated place. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).	
9. Experime controls/nerround protoction		

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Components	Туре	Value	
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m3	
US. OSHA Table Z-1 Permissible E Components	xposure Limits (PEL) for Air Type	Contaminants (29 CFR 1910.1 Value	000) Form
Calcium oxide (CAS 1305-78-8)	PEL	5 mg/m3	
Calcium sulfate (CAS 7778-18-9)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Limestone (CAS 1317-65-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Magnesium Oxide (CAS 1309-48-4)	PEL	15 mg/m3	Total particulate.
US. OSHA Table Z-3 Permissible E Components	xposure Limits (PEL) for Min Type	eral Dusts (29 CFR 1910.1000 Value) Form
Calcium sulfate (CAS 7778-18-9)	TWA	5 mg/m3	Respirable fraction.
,		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Magnesium Oxide (CAS 1309-48-4)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
		2.4 mppcf	Respirable.

Components	Туре	Value	Form
Calcium oxide (CAS 1305-78-8)	TWA	2 mg/m3	
Calcium sulfate (CAS 7778-18-9)	TWA	10 mg/m3	Inhalable fraction.
Magnesium Oxide (CAS 1309-48-4)	TWA	10 mg/m3	Inhalable fraction.
Quartz (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
NIOSH. Immediately Danger Components	ous to Life or Health (IDLH) Values, a Type	as amended Value	
Calcium oxide (CAS 1305-78-8)	IDLH	25 mg/m3	
Magnesium Oxide (CAS 1309-48-4)	IDLH	750 mg/m3	
Quartz (CAS 14808-60-7)	IDLH	50 mg/m3	
US. NIOSH: Pocket Guide to Components	Chemical Hazards Type	Value	Form
Calcium oxide (CAS 1305-78-8)	TWA	2 mg/m3	
Calcium sulfate (CAS 7778-18-9)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Limestone (CAS 1317-65-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total
Quartz (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.
logical limit values	No biological exposure limits noted for	or the ingredient(s).	
oosure guidelines	Occupational exposure to nuisance dust (total and respirable) and respirable crystalline silica should be monitored and controlled.		
propriate engineering htrols	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station and safety shower.		
ividual protection measures, Eye/face protection	such as personal protective equipm Wear safety glasses with side shields		
Skin protection Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.		
Skin protection Other	Wear appropriate chemical resistant of	clothing. Use of an impervious a	apron is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.		
Thermal hazards	Wear appropriate thermal protective of	clothing, when necessary.	
neral hygiene siderations	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		

Appearance Physical state Solid. Powder. Form

Color	Gray to black. Tan. / Brown.
Odor	Odorless.
Odor threshold	Not applicable.
рН	8 - 11
pH concentration	Property has not been measured.
Melting point/freezing point	Property has not been measured.
Initial boiling point and boiling range	> 1832 °F (> 1000 °C)
Flash point	Not applicable, material is a solid.
Evaporation rate	Not applicable, material is a solid.
Flammability (solid, gas)	The product is non-combustible.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	Not applicable, material is a solid.
Explosive limit - upper (%)	Not applicable, material is a solid.
Vapor pressure	Property has not been measured.
Vapor pressure temp.	Property has not been measured.
Vapor density	Not applicable, material is a solid.
Relative density	3 - 3.2
Relative density temperature	Property has not been measured.
Solubility(ies)	
Solubility (water)	Slightly soluble
Partition coefficient (n-octanol/water)	Not applicable for inorganic substances.
Auto-ignition temperature	Not applicable, material is a solid.
Decomposition temperature	Property has not been measured.
Viscosity	Not applicable, material is a solid.
Other information	
Density	Property has not been measured.
Explosive properties	Not explosive.
Kinematic viscosity	Not applicable, material is a solid.
Oxidizing properties	Not oxidizing.
Particle size	Property has not been measured.
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous	No dangerous reaction known under conditions of normal use.

Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Acids. Powerful oxidizers. Aluminum. Chlorine. Fluorine. Phosphorus. Ammonium salts. Aluminum metal. Hydrofluoric acid. Water. Boron trifluoride. Chlorine trifluoride. Manganese trioxide. Oxygen difluoride.
Hazardous decomposition	No hazardous decomposition products are known. In the event of fire: See Section 5.

products

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause cancer by inhalation. May cause irritation to the respiratory system.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye damage.
Ingestion	Expected to be a low ingestion hazard.

Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. May cause respiratory irritation. Coughing. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity	Not expected to be acutely toxic.		
Components	Species	Test Results	
Calcium oxide (CAS 1305-78-8)			
<u>Acute</u>			
Oral			
LD50	Rat	> 2000 mg/kg No deaths occured at this concentration.	
Calcium sulfate (CAS 7778-18-9)			
Acute			
Inhalation			
LC50	Rat	> 3.26 mg/l, 4 Hours	
Oral			
LD50	Rat	> 1581 mg/kg	
Quartz (CAS 14808-60-7)			
<u>Chronic</u>			
Inhalation			
LOEC	Human	0.0563 mg/m3	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye damage.		
Respiratory or skin sensitization			
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin se	ensitization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk" (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer by inhalation. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.		
	valuation of Carcinogenicity		
Quartz (CAS 14808-60-7) NTP Report on Carcinogens	-	iic to humans.	
Quartz (CAS 14808-60-7) OSHA Specifically Regulate	Known To Be I Substances (29 CFR 1910.1001-1053)	e Human Carcinogen.	
Quartz (CAS 14808-60-7)			
Reproductive toxicity	This product is not expected to cause reprodu	uctive or developmental effects.	
Specific target organ toxicity - single exposure	May cause respiratory irritation.		
Specific target organ toxicity - repeated exposure	May cause damage to organs (Lungs) through prolonged or repeated exposure by inhalation.		

Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity	Harmful to aquatic life.
Persistence and degradability	The product contains inorganic compounds which are not biodegradable.
Bioaccumulative potential	No data available.
Mobility in soil	The product is slightly soluble in water. Not expected to be mobile in soil.
Other adverse effects	No data available.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (CAS 14808-60-7)

Cancer lung effects immune system effects kidney effects

Toxic Substances Control Act (TSCA)

All components of the mixture on the TSCA 8(b) inventory are designated "active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes chemical

Classified hazard categories	Skin corrosion or irritation Serious eye damage or eye irritation Carcinogenicity Specific target organ toxicity (single or repeated exposure)	
SARA 313 (TRI reporting) Not regulated.		
Other federal regulations		
Clean Air Act (CAA) Sectior	n 112 Hazardous Air Pollutants (HAPs) List	
Not regulated. Clean Air Act (CAA) Sectior	n 112(r) Accidental Release Prevention (40 CFR 68.130)	
Not regulated.		
Safe Drinking Water Act (SDWA)	Not regulated.	
US state regulations		
US. Massachusetts RTK - S	ubstance List	
Calcium oxide (CAS 130 Calcium sulfate (CAS 77 Limestone (CAS 1317-65 Magnesium Oxide (CAS Quartz (CAS 14808-60-7	78-18-9) 5-3) 1309-48-4)	
	Community Right-to-Know Act	
Calcium oxide (CAS 130 Calcium sulfate (CAS 77 Limestone (CAS 1317-65 Magnesium Oxide (CAS Quartz (CAS 14808-60-7 US. Pennsylvania Worker a	78-18-9) 5-3) 1309-48-4)	
Calcium oxide (CAS 130 Calcium sulfate (CAS 77 Limestone (CAS 1317-65 Magnesium Oxide (CAS Quartz (CAS 14808-60-7 US. Rhode Island RTK	78-18-9) 5-3) 1309-48-4)	
Calcium oxide (CAS 130 Calcium sulfate (CAS 77 Limestone (CAS 1317-65 Magnesium Oxide (CAS Quartz (CAS 14808-60-7	78-18-9) 5-3) 1309-48-4)	
California Proposition 65		
WARNING: Th Fo	his product can expose you to Quartz, which is known to the State of Californi or more information go to www.P65Warnings.ca.gov.	a to cause cancer.
California Proposition 6	65 - CRT: Listed date/Carcinogenic substance	
Quartz (CAS 14808-	-	
International Inventories		
Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

Country(s) or region

Inventory name United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date	14-May-2025
Revision date	-
Version #	01
HMIS® ratings	Health: 3* Flammability: 0 Physical hazard: 0
Disclaimer	Amrize Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.