# SAFETY DATA SHEET



# 1. Identification

Product identifier	Natural Pozzolan SCM			
Other means of identification	Natural Pozzolali SCM			
Product code	Class N, Type N			
Synonyms	TS100, pumice, calcined shale, calcined bentonite, metakaolin, volcanic ash, tuff			
Recommended use	Construction.			
Recommended restrictions				
Neconiniended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations. Uses other than the recommended use.			
Manufacturer/Importer/Supplier/	Distributor information			
Company Name	Amrize Inc.			
Address	8700 W Bryn Mawr Ave, Suite 300			
	Chicago, IL 60631			
Telephone	(773) 372-1000			
Website	www.amrize.com			
E-mail	sdsinfo@amrize.com			
Emergency Telephone Number	CHEMTREC within USA and Canada: 1-800-	424-9300		
	CHEMTREC outside USA and Canada: +1 70	03-527-3887 (collect calls accepted)		
2. Hazard(s) identification				
Physical hazards	Not classified.			
Health hazards	Skin corrosion/irritation	Category 2		
	Serious eye damage/eye irritation	Category 1		
	Carcinogenicity (inhalation)	Category 1A		
	Specific target organ toxicity, repeated exposure (inhalation)	Category 2 (Lungs)		
OSHA defined hazards	Not classified.			
Label elements				
Signal word	Danger			
Hazard statement	Causes skin irritation. Causes serious eye damage. May cause cancer by inhalation. May cause damage to organs (Lungs) through prolonged or repeated exposure by inhalation.			
Precautionary statement				
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection.			
Response	If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a poison center/doctor. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.			
Storage	Store locked up.			
Disposal	Dispose of contents/container in accordance	with local/regional/national/international regulations.		
Hazard(s) not otherwise classified (HNOC)	None known.			

# 3. Composition/information on ingredients

Mixtures			
Chemical name	CAS number	%	
Silicon dioxide, crystalline silica	-free 7631-86-9	50 - 70	
Aluminium Oxide	1344-28-1	12 - 45	
Calcium oxide	1305-78-8	1 - 10	
Calcium sulfate dihydrate	13397-24-5	0.1 - 10	
Quartz	14808-60-7	0.1 - 5	
Magnesium Oxide	1309-48-4	0.1 - 4	
Composition comments	All concentrations are in percent by weight. Any concentration shown as confidentiality or is due to batch variation.	a range is to protect	
4. First-aid measures			
Inhalation	Move to fresh air. If not breathing, give artificial respiration. Call a physic or persist.	ian if symptoms develop	
Skin contact	Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.		
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention immediately.		
Ingestion	Rinse mouth. Get medical attention if symptoms occur.		
Most important symptoms/effects, acute and delayed	Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.		
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep v Symptoms may be delayed.	ictim under observation.	
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwe (show the label where possible). Ensure that medical personnel are awa involved, and take precautions to protect themselves.		
5. Fire-fighting measures			
Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).		
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.		
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed. Combustion procoxides.	lucts may include: Carbo	
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be v	vorn in case of fire.	
Fire fighting equipment/instructions	Use water spray to cool unopened containers.		
Specific methods	Use standard firefighting procedures and consider the hazards of other i	nvolved materials.	
General fire hazards	Will burn if involved in a fire.		
6. Accidental release meas	sures		
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind appropriate protective equipment and clothing during clean-up. Do not b damaged containers or spilled material unless wearing appropriate prote adequate ventilation. Local authorities should be advised if significant sp contained. For personal protection, see section 8 of the SDS.	reathe dust. Do not toucl ective clothing. Ensure	
Methods and materials for containment and cleaning up	Large Spills: Stop the flow of material, if this is without risk. Following prowith water.	oduct recovery, flush are	
	Small Spills: Clean surface thoroughly to remove residual contamination		

Small Spills: Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled<br/>containers. For waste disposal, see section 13 of the SDS.Environmental precautionsAvoid discharge into drains, water courses or onto the ground.

Natural Pozzolan SCM 971841 Version #: 01 Revision date: - Issue date: 20-May-2025

# 7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Do not get this material in contact with eyes. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

#### 8. Exposure controls/personal protection

#### **Occupational exposure limits** U.S. - OSHA Components Type Value Silicon dioxide, crystalline TWA 80 mg/m3 silica-free (CAS 7631-86-9) US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053) Components Type Value Quartz (CAS 14808-60-7) TWA 0.05 mg/m3 US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000) Form Components Value Type Aluminium Oxide (CAS PEL 5 mg/m3 Respirable fraction. 1344-28-1) 15 mg/m3 Total dust. Calcium oxide (CAS PEL 5 mg/m3 1305-78-8) PEL 5 mg/m3 Calcium sulfate dihydrate Respirable fraction. (CAS 13397-24-5) 15 mg/m3 Total dust. Magnesium Oxide (CAS PEL 15 mg/m3 Total particulate. 1309-48-4) US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000) Form Components Type Value Aluminium Oxide (CAS TWA 5 mg/m3 Respirable fraction. 1344-28-1) 15 mg/m3 Total dust. 50 mppcf Total dust. 15 mppcf Respirable fraction. Calcium sulfate dihydrate TWA Respirable fraction. 5 mg/m3 (CAS 13397-24-5) 15 mg/m3 Total dust. Total dust. 50 mppcf 15 mppcf Respirable fraction. Magnesium Oxide (CAS TWA 5 mg/m3 Respirable fraction. 1309-48-4) 15 mg/m3 Total dust. Total dust. 50 mppcf 15 mppcf Respirable fraction. Quartz (CAS 14808-60-7) TWA 0.1 mg/m3 Respirable. 2.4 mppcf Respirable. Silicon dioxide, crystalline TWA 5 mg/m3 Respirable fraction. silica-free (CAS 7631-86-9) 15 mg/m3 Total dust. 20 mppcf

Components		Туре		Value	Form
Aluminium Oxide (CAS 1344-28-1)		TWA		1 mg/m3	Respirable fraction.
Calcium oxide (CAS 1305-78-8)		TWA		2 mg/m3	
Calcium sulfate dihydrate (CAS 13397-24-5)		TWA		10 mg/m3	Inhalable fraction.
Magnesium Oxide (CAS 1309-48-4)		TWA		10 mg/m3	Inhalable fraction.
Quartz (CAS 14808-60-7)		TWA		0.025 mg/m3	Respirable fraction.
NIOSH. Immediately Dange Components	rous to Life or	Health (IDLH) Values, Type		Value	
Calcium oxide (CAS 1305-78-8)		IDLH		25 mg/m3	
Magnesium Oxide (CAS 1309-48-4)		IDLH		750 mg/m3	
Quartz (CAS 14808-60-7)		IDLH		50 mg/m3	
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)		IDLH		3000 mg/m3	
US. NIOSH: Pocket Guide to Components	o Chemical Haz	zards Type		Value	Form
Calcium oxide (CAS 1305-78-8)		TWA		2 mg/m3	
Calcium sulfate dihydrate (CAS 13397-24-5)		TWA		5 mg/m3	Respirable.
				10 mg/m3	Total
Quartz (CAS 14808-60-7)		TWA		0.05 mg/m3	Respirable dust.
Silicon dioxide, crystalline silica-free (CAS 7631-86-9)		TWA		6 mg/m3	
logical limit values	No biological	exposure limits noted f	or the ingredien	t(s).	
osure guidelines		exposure to nuisance onitored and controlled.	dust (total and r	espirable) and re	espirable crystalline silica
propriate engineering trols	applicable, us maintain airbo	se process enclosures, orne levels below recor	local exhaust ve nmended expos	entilation, or othe sure limits. If exp	e matched to conditions. If er engineering controls to osure limits have not bee eyewash station and safe
vidual protection measures, Eye/face protection		onal protective equipn glasses with side shield		nd a face shield	
Skin protection Hand protection	Wear approp supplier.	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.			
Skin protection Other	Wear approp	riate chemical resistant	clothing. Use o	f an impervious	apron is recommended.
			-		-
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR 1910.134.				
Thermal hazards	Wear approp	riate thermal protective	clothing, when	necessary.	
ieral hygiene siderations	measures, su	medical surveillance re ich as washing after ha utinely wash work cloth			

# 9. Physical and chemical properties

Appearance

Physical state	Solid.
Physical state Form	Powder.
Color	Gray to tan. Brown.
Odor	Odorless.
Odor threshold	Not applicable.
pH	8 - 11
pH concentration	Property has not been measured.
Melting point/freezing point	Property has not been measured.
Initial boiling point and boiling	1832 °F (1000 °C)
range	
Flash point	Not applicable, material is a solid.
Evaporation rate	Not applicable, material is a solid.
Flammability (solid, gas)	Will burn if involved in a fire.
Upper/lower flammability or exp	losive limits
Explosive limit - lower (%)	Not applicable, material is a solid.
Explosive limit - upper (%)	Not applicable, material is a solid.
Vapor pressure	Property has not been measured.
Vapor pressure temp.	Property has not been measured.
Vapor density	Not applicable, material is a solid.
Relative density	2.1 - 2.8
Relative density temperature	Property has not been measured.
Solubility(ies)	
Solubility (water)	Slightly soluble
Partition coefficient (n-octanol/water)	Not applicable for inorganic substances.
Auto-ignition temperature	Not applicable, material is a solid.
Decomposition temperature	Property has not been measured.
Viscosity	Not applicable, material is a solid.
Other information	
Density	Property has not been measured.
Density Explosive properties	Property has not been measured. Not explosive.
-	
Explosive properties	Not explosive.
Explosive properties Kinematic viscosity	Not applicable, material is a solid.
Explosive properties Kinematic viscosity Oxidizing properties	Not explosive. Not applicable, material is a solid. Not oxidizing. Property has not been measured.
Explosive properties Kinematic viscosity Oxidizing properties Particle size	Not explosive. Not applicable, material is a solid. Not oxidizing. Property has not been measured.
Explosive properties Kinematic viscosity Oxidizing properties Particle size 10. Stability and reactivity	Not explosive. Not applicable, material is a solid. Not oxidizing. Property has not been measured.

reactions	
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Acids. Strong bases. Powerful oxidizers. Aluminum. Chlorine. Fluorine. Phosphorus.
Hazardous decomposition products	No hazardous decomposition products are known.

# 11. Toxicological information

# Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause cancer by inhalation.
Skin contact	Causes skin irritation.
Eye contact	Causes serious eye damage.
Ingestion	May cause discomfort if swallowed.

Natural Pozzolan SCM

Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

#### Information on toxicological effects

Acute toxicity	Not known.		
Components	Species	Test Results	
Aluminium Oxide (CAS 1344-28-1)	)		
Acute			
Inhalation			
LC50	Rat	> 2.3 mg/l, 4 Hours	
Calcium oxide (CAS 1305-78-8)			
Acute			
Oral			
LD50	Rat	> 2000 mg/kg No deaths occured at this concentration.	
Quartz (CAS 14808-60-7)			
<u>Chronic</u>			
Inhalation			
LOEC	Human	0.0563 mg/m3	
Silicon dioxide, crystalline silica-fre	e (CAS 7631-86-9)		
Acute			
Dermal			
LD50	Rabbit	> 5000 mg/kg, 24 Hours	
Inhalation Dust			
LC50	Rat	> 0.14 mg/l, 4 Hours	
Oral		- 0.14 mg/l, 4 Hours	
LD50	Rat	> 3300 mg/kg	
Skin corrosion/irritation	Causes skin irritation.		
Serious eye damage/eye irritation	Causes serious eye damage.		
Respiratory or skin sensitization			
Respiratory sensitization	Not a respiratory sensitizer.		
Skin sensitization	This product is not expected to cause skin sensit	ization.	
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.		
Carcinogenicity	In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk" (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer by inhalation. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.		

Quartz (CAS 14808-60-7) Silicon dioxide, crystalline silica-free (CAS 7631-86-9) 1 Carcinogenic to humans.

3 Not classifiable as to carcinogenicity to humans.

NTP Report on Carcinogens	
Quartz (CAS 14808-60-7)	Known To Be Human Carcinogen.
OSHA Specifically Regulated	d Substances (29 CFR 1910.1001-1053)
Quartz (CAS 14808-60-7)	Cancer
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	May cause damage to organs (Lungs) through prolonged or repeated exposure by inhalation.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged inhalation may be harmful. May cause damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.

# 12. Ecological information

Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.			
Components		Species Test Results		
Calcium sulfate dihydrate (C	AS 13397-24-5)			
Aquatic				
Fish	LC50	Fathead minnow (Pim	ephales promelas)	> 1970 mg/l, 96 hours
Persistence and degradability	The product contains inorganic compounds which are not biodegradable.			
Bioaccumulative potential	No data available.			
Mobility in soil	No data availa	able.		
Other adverse effects	No data availa	able.		

### 13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport information

#### DOT

Not regulated as dangerous goods.

#### ΙΑΤΑ

Not regulated as dangerous goods.

#### IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and

the IBC Code

# 15. Regulatory information

#### **US federal regulations**

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

#### SARA 304 Emergency release notification

OSHA Specifically Reg Quartz (CAS 14808-		29 CFR 1910.1001-1053) Cancer lung effects immune syste kidney effects		
Toxic Substances Control A	Act (TSCA)	All components of the "active".	mixture on the TSCA 8(b) invento	ory are designated
Superfund Amendments and Re SARA 302 Extremely hazard Not listed.		1986 (SARA)		
SARA 311/312 Hazardous chemical	Yes			
Classified hazard categories	Skin corrosion or irr Serious eye damage Carcinogenicity Specific target organ		ed exposure)	
SARA 313 (TRI reporting) Chemical name		CAS number	% by wt.	
Aluminium Oxide		1344-28-1	12 - 45	
Other federal regulations		1044-20-1	12 - 40	
Clean Air Act (CAA) Section	n 112 Hazardous Air I	Pollutants (HAPs) List		
Not regulated. Clean Air Act (CAA) Section			FR 68.130)	
Not regulated.				
Safe Drinking Water Act (SDWA)	Not regulated.			
US state regulations				
US. Massachusetts RTK - S	ubstance List			
Aluminium Oxide (CAS 1 Calcium oxide (CAS 130 Calcium sulfate dihydrate Magnesium Oxide (CAS Quartz (CAS 14808-60-7 Silicon dioxide, crystallin	5-78-8) e (CAS 13397-24-5) 1309-48-4) ) e silica-free (CAS 763			
US. New Jersey Worker and Aluminium Oxide (CAS 1		o-Know Act		
Calcium oxide (CAS 130 Calcium oxide (CAS 130 Calcium sulfate dihydrate Magnesium Oxide (CAS Quartz (CAS 14808-60-7	5-78-8) e (CAS 13397-24-5) 1309-48-4)			
US. Pennsylvania Worker a		-to-Know Law		
Aluminium Oxide (CAS 1 Calcium oxide (CAS 130 Calcium sulfate dihydrate Magnesium Oxide (CAS Quartz (CAS 14808-60-7 Silicon dioxide, crystalling	5-78-8) e (CAS 13397-24-5) 1309-48-4) )	1-86-9)		
US. Rhode Island RTK				
Aluminium Oxide (CAS 1 Calcium oxide (CAS 130 Calcium sulfate dihydrate Magnesium Oxide (CAS Quartz (CAS 14808-60-7 Silicon dioxide, crystalling	5-78-8) e (CAS 13397-24-5) 1309-48-4) )	1-86-9)		
California Proposition 65	( -·· · - · · • • •	,		
		e you to Quartz, which is k to www.P65Warnings.ca	nown to the State of California to gov.	cause cancer.

#### California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (CAS 14808-60-7)

Listed: October 1, 1988

#### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

# 16. Other information, including date of preparation or last revision

Issue date	20-May-2025
Revision date	-
Version #	01
HMIS® ratings	Health: 3* Flammability: 1 Physical hazard: 0
Disclaimer	Amrize Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.