SAFETY DATA SHEET



1. Identification

Product identifier Reclaimed Asphalt Pavement

Other means of identification

Synonyms Reclaimed Asphalt Pavement, RAP, Crusted Asphalt Base Course, Reclaimed Paving Material,

Reclaimed Blacktop, Reclaimed Asphalt Concrete, and Recycled Asphalt Pavement

Recommended use Construction.

Recommended restrictions Workers (and your customers or users in the case of resale) should be informed of the potential

presence of respirable dust and respirable crystalline silica as well as their potential hazards.

Appropriate training in the proper use and handling of this material should be provided as required

under applicable regulations. Uses other than the recommended use.

Manufacturer/Importer/Supplier/Distributor information

Company Name Amrize Inc.

Address 8700 W Bryn Mawr Ave, Suite 300

Chicago, IL 60631

Telephone (773) 372-1000

Website www.amrize.com

E-mail sdsinfo@amrize.com

Emergency Telephone

Number

CHEMTREC within USA and Canada: 1-800-424-9300

CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Carcinogenicity (inhalation) Category 1A

Specific target organ toxicity, repeated Category 2 (Lungs)

exposure (inhalation)

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause cancer by inhalation. May cause damage to organs (Lungs) through prolonged or

repeated exposure by inhalation.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust. Wear protective gloves/protective clothing/eye

protection/face protection.

Response If exposed or concerned: Get medical advice/attention.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

Supplemental information None.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Limestone	1317-65-3	90 - 95
Asphalt	8052-42-4	< 10
Quartz	14808-60-7	5 - 10

Composition comments

All concentrations are in percent by weight. Any concentration shown as a range is to protect confidentiality or is due to batch variation.

4. First-aid measures

Inhalation

Move to fresh air. If not breathing, give artificial respiration. Call a physician if symptoms develop

or persist.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eve contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Coughing. Prolonged exposure may cause chronic effects.

Indication of immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

General information

IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from the chemical

During fire, gases hazardous to health may be formed. Combustion products may include: Carbon oxides. Smoke. Fumes. Hydrocarbons. Sulfur oxides. Nitrogen oxides. Hydrogen sulfide.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials. Specific methods

No unusual fire or explosion hazards noted. General fire hazards

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up The product is immiscible with water and will sediment in water systems. Stop the flow of material, if this is without risk. Following product recovery, flush area with water. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS. The product is insoluble in water.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store in tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Specifically Regulation Components		Type		,	Value	
Quartz (CAS 14808-60-7)		TWA			0.05 mg/m3	
US. OSHA Table Z-1 Permis Components	sible Exposure	Limits	s (PEL) for Air Co	ntaminants	(29 CFR 1910.10 Value	000) Form
Limestone (CAS 1317-65-3)		PEL			5 mg/m3	Respirable fraction.
					15 mg/m3	Total dust.
US. OSHA Table Z-3 Permis Components	sible Exposure	Limits	s (PEL) for Minera	ıl Dusts (29	CFR 1910.1000) Value	Form
Limestone (CAS 1317-65-3)		TWA			5 mg/m3	Respirable fraction.
					15 mg/m3	Total dust.
					50 mppcf	Total dust.
					15 mppcf	Respirable fraction.
Quartz (CAS 14808-60-7)		TWA			0.1 mg/m3	Respirable.
					2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Components	Values (TLV)	Туре			Value	Form
Asphalt (CAS 8052-42-4)		TWA			0.5 mg/m3	Inhalable fume.
Quartz (CAS 14808-60-7)		TWA			0.025 mg/m3	Respirable fraction.
NIOSH. Immediately Dange Components	rous to Life or I	Health Type	(IDLH) Values, as	amended	Value	
Quartz (CAS 14808-60-7)		IDLH			50 mg/m3	
US. NIOSH: Pocket Guide to Components	o Chemical Haz	ards Type			Value	Form
Asphalt (CAS 8052-42-4)		Ceilin	g		5 mg/m3	Fume.
Limestone (CAS 1317-65-3)		TWA			5 mg/m3	Respirable.
					10 mg/m3	Total
Quartz (CAS 14808-60-7)		TWA			0.05 mg/m3	Respirable dust.
ogical limit values						
ACGIH Biological Exposure	Indices (BEI) /alue		Determinant	Specime	n Sampling	Time
	2.5 μg/l 		1-Hydroxypyre ne, with hydrolysis (1-HP)	Urine	*	
* - For sampling details, pleas						andmakela a COP OF
osure guidelines	should be mo	nitored	and controlled.	•	. ,	espirable crystalline silica
ropriate engineering trols	Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.					
vidual protection measures, Eye/face protection	-	-	otective equipments with side shields (
Skin protection Hand protection	Wear appropr	iate ch	emical resistant de	oves. Suitab	le gloves can be r	recommended by the glov

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA 29 CFR

1910.134.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state Solid.

Form Solid. Various shapes and sizes.

Color Black.

Odor Slight petroleum odor.

Odor threshold Property has not been measured.

range

Flash point

Not applicable, material is a solid.

Evaporation rate

Not applicable, material is a solid.

Flammability (solid, gas)

The product is non-combustible.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not applicable, material is a solid.

Explosive limit - upper (%) Not applicable, material is a solid.

Vapor pressure Property has not been measured.

Vapor density Property has not been measured.

Not applicable, material is a solid.

Relative density 2 - 2.5

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient Not applicable, product is a mixture.

(n-octanol/water)

Auto-ignition temperature

Not applicable, material is a solid.

Property has not been measured.

Viscosity

Not applicable, material is a solid.

Other information

Density Property has not been measured.

Explosive properties Not explosive.

Kinematic viscosity Not applicable, material is a solid.

Oxidizing properties Not oxidizing.

Particle size Property has not been measured.

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoidContact with incompatible materials.

Incompatible materials Acids. Powerful oxidizers. Chlorine. Fluorine. Strong bases. Nitrates. Chlorates. Peroxides. When

molten: Water.

Hazardous decomposition

products

No hazardous decomposition products are known. In the event of fire: See Section 5.

11. Toxicological information

Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

cancer by inhalation.

Skin contact Prolonged skin contact may cause temporary irritation. **Eve contact** Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics Coughing. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test Results
Asphalt (CAS 8052-42-4)		
<u>Acute</u>		
Dermal		
LD50	Rabbit	> 2000 mg/kg, 24 Hours
Oral		
LD50	Rat	> 5000 mg/kg
Quartz (CAS 14808-60-7)		
<u>Chronic</u>		
Inhalation		
LOEC	Human	0.0563 mg/m3

Prolonged skin contact may cause temporary irritation. Skin corrosion/irritation Direct contact with eyes may cause temporary irritation. Serious eye damage/eye

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

This product is not expected to cause skin sensitization. Skin sensitization

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica Carcinogenicity

inhaled from occupational sources can cause lung cancer in humans. However in making the

overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial

respirable dust and respirable crystalline silica should be monitored and controlled.

circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk..." (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer by inhalation. Occupational exposure to

IARC Monographs. Overall Evaluation of Carcinogenicity

2B Possibly carcinogenic to humans. Asphalt (CAS 8052-42-4)

Quartz (CAS 14808-60-7) 1 Carcinogenic to humans.

NTP Report on Carcinogens

Asphalt (CAS 8052-42-4) Known To Be Human Carcinogen.

Quartz (CAS 14808-60-7) Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (CAS 14808-60-7) Cancer

Reproductive toxicityThis product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (Lungs) through prolonged or repeated exposure by inhalation.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged inhalation may be harmful. May cause damage to organs through prolonged or

repeated exposure. Prolonged exposure may cause chronic effects.

12. Ecological information

EcotoxicityThe product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability The product contains inorganic compounds for which biodegradability is not applicable.

Bioaccumulative potential No data available.

Mobility in soil The product is insoluble in water. Not expected to be mobile in soil.

Other adverse effects

This product contains one or more substances identified as hazardous air pollutants (HAPs) per

the US Federal Clean Air Act (see section 15).

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable.

, iO

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Asphalt (CAS 8052-42-4) Listed

SARA 304 Emergency release notification

Not regulated

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Quartz (CAS 14808-60-7) Cancer

lung effects

immune system effects

kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Carcinogenicity

categories Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Asphalt (CAS 8052-42-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Asphalt (CAS 8052-42-4) Limestone (CAS 1317-65-3) Quartz (CAS 14808-60-7)

US. New Jersey Worker and Community Right-to-Know Act

Asphalt (CAS 8052-42-4) Limestone (CAS 1317-65-3) Quartz (CAS 14808-60-7)

US. Pennsylvania Worker and Community Right-to-Know Law

Asphalt (CAS 8052-42-4) Limestone (CAS 1317-65-3) Quartz (CAS 14808-60-7)

US. Rhode Island RTK

Asphalt (CAS 8052-42-4) Limestone (CAS 1317-65-3) Quartz (CAS 14808-60-7)

California Proposition 65



Taiwan

WARNING: This product can expose you to Quartz, which is known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

Taiwan Chemical Substance Inventory (TCSI)

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Quartz (CAS 14808-60-7) Listed: October 1, 1988

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	Yes
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

Reclaimed Asphalt Pavement SDS US

Yes

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 08-May-2025

Revision date - 01

HMIS® ratings Health: 2*

Flammability: 0 Physical hazard: 0

Disclaimer Amrize Inc. cannot anticipate all conditions under which this information and its product, or the

products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the

sheet was written based on the best knowledge and experience currently available.

Reclaimed Asphalt Pavement SDS US

971842 Version #: 01 Revision date: - Issue date: 08-May-2025