

SAFETY DATA SHEET

1. Identification

Product identifier	Manufactured Shingle Modifier (MSM)
Other means of identification	None.
Recommended use	Construction.
Recommended restrictions	Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations. Uses other than the recommended use.

Manufacturer/Importer/Supplier/Distributor information

Company name	Amrize Inc.
Address	6509 Airport Road
	Mississauga, Ontario L4V 157
Telephone	Eastern Canada: (905) 738-7070
	Western Canada: (403) 225-5400
Website	www.amrize.com
E-mail	sdsinfo@amrize.com
Emergency telephone number	CHEMTREC within USA and Canada: 1-800-424-9300
	CHEMTREC outside USA and Canada: +1 703-527-3887 (collect calls accepted)

2. Hazard identification

Physical hazards	Combustible dusts	Category 1
Health hazards	Carcinogenicity (inhalation)	Category 1A
	Specific target organ toxicity - repeated exposure (inhalation)	Category 2 (Lungs)

Label elements



Signal word	Danger
Hazard statement	May form combustible dust concentrations in air. May cause cancer by inhalation. May cause damage to organs (Lungs) through prolonged or repeated exposure by inhalation.
Precautionary statement	
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Prevent dust accumulation to minimize explosion hazard. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Keep container tightly closed. Ground and bond container and receiving equipment. Do not breathe dust. Wear protective gloves/protective clothing/eye protection/face protection. Observe good industrial hygiene practices.
Response	IF exposed or concerned: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to extinguish.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Supplemental information	None.
Other hazards	None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Quartz		14808-60-7	5 - 10
Composition comments	All concentrations are in percent by weight. Components not listed are either non-hazardous or are below reportable limits. Any concentration shown as a range is to protect confidentiality or is due to batch variation.		
4. First-aid measures			
Inhalation	Move to fresh air. If not breathing, give artificial respiration. Call a physician if symptoms develop or persist.		
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.		
Eye contact	Do not rub eyes. Rinse with water. Get medica	l attention if irritation develop	s and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.		
Most important symptoms/effects, acute and delayed	Dusts may irritate the respiratory tract, skin and eyes. Coughing. Prolonged exposure may caus chronic effects.		exposure may cause
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.		
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.		
5. Fire-fighting measures			
Suitable extinguishing media	Avoid high pressure media which could cause the formation of a potentially explosible dust-air mixture. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Apply extinguishing med carefully to avoid creating airborne dust.		
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.		
Specific hazards arising from the chemical	Explosion hazard: Avoid generating dust; fine of in the presence of an ignition source is a poten hazardous to health may be formed. Combustion sulfide. Magnesium oxides. Silicon oxides. Sulf	tial dust explosion hazard. Do on products may include: Car	uring fire, gases
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full pro	tective clothing must be worr	n in case of fire.
Fire fighting equipment/instructions	In case of fire and/or explosion do not breathe so without risk.	fumes. Move containers from	fire area if you can do
Specific methods	Use standard firefighting procedures and consi	der the hazards of other invo	lved materials.
General fire hazards	May form combustible dust concentrations in a	ir.	
6. Accidental release meas	sures		
Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Use only non-sparking tools. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.		urfaces, as these may ent concentration. t breathe dust. Ensure
Methods and materials for containment and cleaning up	Eliminate all ignition sources (no smoking, flare precautionary measures against static discharg dust in the air (i.e., clearing dust surfaces with water and will spread on the water surface. Sto	ge. Use only non-sparking too compressed air). The produc	ls. Avoid dispersal of tis immiscible with
	Large Spills: Wet down with water and dike for container. Following product recovery, flush are		terial into waste

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use. Put material in suitable, covered, labelled
containers. For waste disposal, see section 13 of the SDS. The product is insoluble in water.Environmental precautionsAvoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimise dust generation and accumulation. Avoid significant deposits of material, especially on horizontal surfaces, which may become airborne and form combustible dust clouds and may contribute to secondary explosions. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Keep away from heat/sparks/open flames/hot surfaces No smoking. Combustible dust clouds may be created where operations produce fine material (dust). Handling and processing operations should be conducted in accordance with 'best practices' (e.g. NFPA-654). Explosion-proof general and local exhaust ventilation. Do not breathe dust. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
Conditions for safe storage,	Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away

Conditions for safe storage,
including any incompatibilitiesStore locked up. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away
from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

es (TLV) Type	Value	Form
TWA	0.025 mg/m3	Respirable fraction.
onal Health & Safety Code, Scl	nedule 1, Table 2), as amended	
Туре	Value	Form
TWA	0.025 mg/m3	Respirable particles.
	s for Chemical Substances, Oco	cupational Health and
Туре	Value	Form
TWA	0.025 mg/m3	Respirable fraction.
7/2006, The Workplace Safety	And Health Act), as amended	
Туре	Value	Form
TWA	0.025 mg/m3	Respirable fraction.
	Value	Form
TWA	0.025 mg/m3	Respirable fraction.
of Exposure to Biological or Cl	nemical Agents), as amended	
Туре	Value	Form
TWA	0.1 mg/m3	Respirable fraction.
of Labor - Regulation respecti	ng occupational health and saf	ety)
of Labor - Regulation respecti Type	č	·
of Labor - Regulation respecti	ng occupational health and saf	ety)
of Labor - Regulation respecti Type TWA	ng occupational health and saf Value	ety) Form Respirable dust.
of Labor - Regulation respecti Type TWA ccupational Health and Safety	ng occupational health and saf Value 0.05 mg/m3 Regulations, 1996, Table 21), as	ety) Form Respirable dust.
	Type TWA onal Health & Safety Code, Sch Type TWA (Occupational Exposure Limits ended) Type TWA 17/2006, The Workplace Safety Type TWA Threshold Limit Values (TLVs) I julation 91-191) Type TWA of Exposure to Biological or Cl	TypeValueTWA0.025 mg/m3onal Health & Safety Code, Schedule 1, Table 2), as amended TypeValueTWA0.025 mg/m3(Occupational Exposure Limits for Chemical Substances, Occ ended)TypeValueValueTWA0.025 mg/m3(Occupational Exposure Limits for Chemical Substances, Occ ended)TypeValueValueTWA0.025 mg/m317/2006, The Workplace Safety And Health Act), as amended TypeValueTWA0.025 mg/m317/2006, The Workplace Safety And Health Act), as amended TypeValueTWA0.025 mg/m3Threshold Limit Values (TLVs) Based on the 1991 and 1997 AC Julation 91-191)TypeTWA0.025 mg/m3of Exposure to Biological or Chemical Agents), as amendedTwa

Appropriate engineering controls	Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks.
Individual protection measures,	such as personal protective equipment
Eye/face protection	Wear safety glasses with side shields (or goggles).
Skin protection	
Hand protection	Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.
Other	Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Selection and use of respiratory protective equipment should be in accordance with CSA Standard Z94.4.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
General hygiene considerations	Observe any medical surveillance requirements. When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

-	-	
Physical state	Solid.	
Form	Granular solid.	
Colour	Dark.	
Odour	Slight petroleum odor.	
Odour threshold	Property has not been measured.	
Melting point/freezing point	Property has not been measured.	
Boiling point or initial boiling point and boiling range	> 1000 °C (> 1832 °F)	
Flammability	Combustible dust.	
Upper/lower flammability or exp	losive limits	
Explosive limit - lower (%)	Not applicable, material is a solid.	
Explosive limit – upper (%)	Not applicable, material is a solid.	
Flash point	Not applicable, material is a solid.	
Auto-ignition temperature	Not applicable, material is a solid.	
Decomposition temperature	Property has not been measured.	
рН	Property has not been measured.	
pH concentration	Property has not been measured.	
Kinematic viscosity	Not applicable, material is a solid.	
Solubility		
Solubility (water)	Insoluble	
Partition coefficient (n-octanol/water) (log value)	Not applicable, product is a mixture.	
Vapour pressure	Property has not been measured.	
Density and/or relative density		
Density	Property has not been measured.	
Relative density	Property has not been measured.	
Vapour density	Not applicable, material is a solid.	
Manufactured Shingle Modifier (MSM)		SDS Ca

Particle characteristics	Property has not been measured.
Other information	
Evaporation rate	Not applicable, material is a solid.
Explosive properties	Combustible dust hazard.
Oxidising properties	Not oxidising.
Viscosity	Not applicable, material is a solid.

10. Stability and reactivity

Reactivity Chemical stability	The product is stable and non-reactive under normal conditions of use, storage and transport. Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Keep away from heat, sparks and open flame. Contact with incompatible materials. Minimise dust generation and accumulation.
Incompatible materials	Acids. Strong oxidising agents. Powerful oxidizers. Chlorine. Fluorine. Hydrofluoric acid.
Hazardous decomposition products	No hazardous decomposition products are known. In the event of fire: See Section 5.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. May cause cancer by inhalation.
Skin contact	Prolonged skin contact may cause temporary irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Dusts may irritate the respiratory tract, skin and eyes. Coughing. Prolonged exposure may cause chronic effects.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

ults	
ı/m3	
at greater than 0.1% are	
Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation. n Not a respiratory sensitiser. This product is not expected to cause skin sensitisation. No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.	

Carcinogenicity	In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation, IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) In June 2003, SCOEL (the EU Scientific Committee on Occupational Exposure Limits) concluded that the main effect in humans of the inhalation of respirable crystalline silica dust is silicosis. "There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis (and, apparently, not in employees without silicosis exposed to silica dust in quarries and in the ceramic industry). Therefore, preventing the onset of silicosis will also reduce the cancer risk" (SCOEL SUM Doc 94-final, June 2003) According to the current state of the art, worker protection against silicosis can be consistently assured by respecting the existing regulatory occupational exposure limits. May cause cancer by inhalation. Occupational exposure to respirable dust and respirable crystalline silica should be monitored and controlled.		
ACGIH Carcinogens Quartz (CAS 14808-60-7)		A2 Suspected human carcinogen.	
Canada - Alberta OELs: Card			
Quartz (CAS 14808-60-7)		Suspected human carcinogen.	
Canada - Manitoba OELs: ca	•••		
Quartz (CAS 14808-60-7) Canada - Quebec OELs: Car		Suspected human carcinogen.	
Quartz (CAS 14808-60-7)		Suspected carcinogenic effect in humans.	
,	Evaluation of Carcinogenicity		
Quartz (CAS 14808-60-7)		1 Carcinogenic to humans.	
	gram (NTP) Report on Carcino	-	
Quartz (CAS 14808-60-7)		Known To Be Human Carcinogen.	
Reproductive toxicity		cause reproductive or developmental effects.	
Specific target organ toxicity - single exposure	Not classified.		
Specific target organ toxicity - repeated exposure	May cause damage to organs (Lungs) through prolonged or repeated exposure by inhalation.	
Aspiration hazard	Not an aspiration hazard.		
Chronic effects		armful. May cause damage to organs through prolonged or exposure may cause chronic effects.	
12. Ecological information			
Ecotoxicity	The product is not classified as environmentally hazardous. However, this does not exclude the		
2	possibility that large or frequent spills can have a harmful or damaging effect on the environment.		
Persistence and degradability		anic compounds which are not biodegradable.	
Bioaccumulative potential	No data available.		
Mobility in soil		er. Not expected to be mobile in soil.	
Other adverse effects	No data available.		
13. Disposal consideration	IS		
Disposal instructions		in sealed containers at licensed waste disposal site. Dispose of ce with local/regional/national/international regulations.	
Local disposal regulations	Dispose in accordance with all a	applicable regulations.	
Hazardous waste code	The waste code should be assign disposal company.	gned in discussion between the user, the producer and the waste	
Waste from residues / unused products		ocal regulations. Empty containers or liners may retain some and its container must be disposed of in a safe manner.	
Contaminated packaging		retain product residue, follow label warnings even after container is uld be taken to an approved waste handling site for recycling or	
14. Transport information			
TDC			

TDG

Not regulated as dangerous goods.

ΙΑΤΑ

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

15. Regulatory information

This product has been classified in accordance with the hazard criteria of the HPR and the SDS contains all the information required by the HPR.

Controlled Drugs and Substances Act

Not regulated.

Canadian regulations

Export Control List (CEPA 1999, Schedule 3) Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

Issue date	09-May-2025
Revision date	-
Version No.	01
Further information	Refer to: OSHA 3371-08 2009, Hazard Communication Guidance for Combustible Dusts NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing, Processing, and Handling of Combustible Particulate Solids

Amrize Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.